

Kimball®

ESSENCE  
ULTRALEATHER® | ORIGINAL

FAUX LEATHER



3692 Admiral




3617 White



3691 Pelican



3636 Chamois



3612 Red



3615 Dove Grey




3614 Stone



3683 Pecan



3640 Garnet




3684 Charcoal




3690 Papyrus



3667 Taupe



3679 Raven



3663 Walnut

Note: Refer to back of card for specifications.

## Specifications

Grade 6

Composition surface	100% Polycarbonate Polyurethane Surface
backing	100% Reinforced Rayon Backing
Width	54"
Weight	Approx. 9.7 oz. per square yard Approx. 14.6 oz. per linear yard
Thickness	Approx. 0.95 Millimetres
Repeat	None
Finish	None

## Performance

Abrasion	ASTM D4157 / 400,000 Double Rubs (Wyzenbeek)* BS EN ISO 12947-2 / 180,000 Rubs (Martindale)**
Light Fastness	AATCC 16.3, 200 Hours, Grade 4
Hydrolysis	14+ Weeks ASTM D3690 Sect. 6.11 (Hydrolytic Stability) ISO 1419 Method C (Accelerated Ageing)
Color Fastness	AATCC 8, Grade 4-5 Wet & Dry
Adhesion of Coating	ASTM D751
Tear Strength	ASTM D2261
Breaking Strength	ASTM D5034

## Flammability

ASTM E84 (Adhered)	Class A	FMVSS 302 & 95/28 Annex IV	Pass
CA TB 117	Pass	UFAC	Class 1
NFPA 260	Class 1		

## Cleaning and Care Instructions

- Wipe up spills as soon as they occur
- Clean with soap and water or alcohol based cleaners
- Sanitize using (1:5) bleach/water solution or other approved disinfectants
- For stubborn stains, wipe off with isopropyl alcohol as soon as possible
- Thoroughly rinse all solution residue with clean water
- Air dry

## Certificates and Standards

For more information on certifications and standards, sustainability, as well as cleaning and care instructions, please visit our website.

Product details and other data are subject to change without notice. We will always ship a satisfactory commercial color match. Due to industry standard dye lot variation, colors may not match exactly. Cut yardage and individual samples are available. Please visit [ultrafabricsinc.com](http://ultrafabricsinc.com) to order samples.