

Price List Effective Dates:

Pricing	10.03.22
Revisions	09.01.22



▶ See page


Statement of Line	PL.2
Planning	PL.3
Freestanding & Surface-Mount LED Lights	PL.3
LED Task Lights	PL.4
Pricing	
Freestanding & Surface-Mount LED Lights	PL.5
LED Task Lights	PL.6

Statement of Line	▶ See page PL.2
Planning	PL.3
Pricing	PL.5




LED Freestanding Lights

- ▶ See page PL.3 for product info.
- ▶ See page PL.5 to specify.



LED Surface-Mount Lights

- ▶ See page PL.3 for product info.
- ▶ See page PL.5 to specify.



LED Task Lights

- ▶ See page PL.4 for product info.
- ▶ See page PL.6 to specify.


PERKS® LIGHTING

Freestanding & Surface-Mount LED Lights


Planning

Statement of Line	▶ See page PL.2
Planning	PL.3
Pricing	PL.5


Details




Freestanding LED light includes touch sensor switch on the head of the lamp. Push the red switch to turn on light. Hold the switch down and the light will dim to its lowest cycle and then start to brighten again. Release the switch when the light intensity is at the desired level.




Arm on freestanding light swivels 350°.




Hinge on freestanding light allows light to be turned straight up.



Head on freestanding light rotates 360° allowing the light to be directed to any angle.



Head on surface-mount light rotates 360° allowing the light to be directed to any angle.



Surface-mount LED light is field installed. Available for use with surfaces from 3/4" to 1 9/16" thick. The on/off touch switch is incorporated into the light.

- 3-year warranty
- 50,000 hour LED life
- U.L. listed power supply
- Mercury, lead and UV free
- Kelvin—3500K

PERKS® LIGHTING

LED Task Lights

Details

LED task lights are a thin-profile solution for overhead cabinets, highback organizers, and shelves. LEDs are mercury-free and consume less power.

Linear body features a metal trough reflector with diffuser lens. The body is silver anodized aluminum with white plastic end caps.


Single-touch on/off and touch-and-hold continuous dimming pad with last state memory will be remembered for the next time the fixture is turned on.

Automatic turn-off feature comes standard and will turn the fixture off after 10 hours of continuous use.

Number of LED lights varies by fixture width:
 17"W models include 24 LEDs
 31"W models include 48 LEDs
 44"W models include 72 LEDs


LED specifications:

- LED lifespan: 50,000 hours
- Color temperature: 3500K
- Color rendering index: 83
- ETL listed; compliant to UL 153 & CSA C22.2 No. 9



Single/starter unit includes:

- Fixture
- Two-piece 12' black cord with an inline 4½"W x 2⅛"D x 1⅞"H 65-watt brick power supply with plug
- Mounting kit



Add-on unit includes:

- Fixture
- One 8" black interconnect cord
- One 30" black interconnect cord
- Two adhesive managers
- Mounting kit



Optional occupancy sensor, available separately, turns the fixture off after 30 minutes of inactivity and back on again as the user enters the workspace. If occupant is present, the light will remain on. Occupancy sensor model includes:

- Sensor
- 1" connector pin
- Mounting kit

Connections


Power cords and interconnect cords can be plugged into either end of the fixture. Interconnect cord utilizes independent switching; each fixture must be turned on and off individually.

Mounting kits, standard with each task light unit, include:

- Two screw-mount clip/screws
- Two magnetic-mount clip/magnets
- Two adhesive cord managers



Only one occupancy sensor is required per interconnected (daisy chained) run of fixtures to turn all fixtures on and off automatically. The power supply must connect to the occupancy sensor, followed by the connector pin, then the single/starter unit as shown above.



Interconnect (daisy chain) application requires one single/starter unit and add-on units. Total wattage must not exceed 54 watts for the full run.
 ▶ See *Interconnect Guide* at right.

Planning

Statement of Line	▶ See page PL.2
Planning	PL.3
Pricing	PL.5

Interconnect Guide:

Task Light Length	Watts per Unit	Max. No. of Units	Total Watts
17"	8	6	48
31"	18	3	54
44"	26	2	52

IMPORTANT: Different task light lengths can be combined in the chain; however, the total wattage cannot exceed 54. For example, one 17" unit (8 watts) plus one 44" unit (26 watts) = 34 watts which is below the maximum.

PERKS® LIGHTING

LED Freestanding and Surface-Mount Lights


Pricing

GSA Non-Contract

Statement of Line	▶ See page PL.2
Planning	PL.3
Pricing	PL.5



<i>W</i>	<i>H</i>	<i>Base Diameter</i>	<i>Model</i>	<i>Price</i>
Freestanding				
16 ¹ / ₈ "	15 ¹⁵ / ₁₆ "	6 ¹ / ₈ "	KCUFSL	\$404



Surface Mount				
37 ³ / ₁₆ "	13 ⁷ / ₁₆ "		KCUSML	\$551

Standard Includes

- Fixture
- Power supply
- 6 foot cord



How to Specify

- 1 Model

PERKS® LIGHTING
LED Task Lights

Pricing
GSA SIN 33721

Statement of Line	▶ See page PL.2
Planning	PL.3
Pricing	PL.5



<i>D</i>	<i>W</i>	<i>H</i>	<i>Model</i>	<i>Description</i>	<i>Price</i>
Single/Starter Units					
2"	17"	1/2"	99K17TLS	24 LED lights	\$382
2"	31"	1/2"	99K31TLS	48 LED lights	548
2"	44"	1/2"	99K44TLS	72 LED lights	711
Add-On Interconnect Units					
2"	17"	1/2"	99K17TLA	24 LED lights	\$369
2"	31"	1/2"	99K31TLA	48 LED lights	530
2"	44"	1/2"	99K44TLA	72 LED lights	694
Related Products:					
Occupancy Sensor					
2"	2 1/4"	3/4"	99KTLOS		\$254

Standard Includes

Starter Unit

- Fixture
- Two-piece 12' black cord with an inline 4 1/2"W x 2 1/8"D x 1 1/8"H 65-watt brick power supply and plug
- Mounting kit

Add-On Unit

- Fixture
- One 8" black interconnect cord
- One 30" black interconnect cord
- Mounting kit
- Two adhesive managers

Sensor

- Sensor
- 1" connector pin
- Mounting kit

Tips

Interconnect (Daisy Chain) Guide
▶ See page PL.4.

How to Specify

- ① Model